



WATER HEATERS WITH HEAT EXCHANGER (S) FOR VERTICAL MOUNTING ON THE WALL

CHARACTERISTICS

Model	...	72268S	72270S	72266S	72280MS	72280S	72281S
Rated volume	L	80	100	120	150	150	200
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,8	0,8
Rated voltage	V~	230	230	230	230	230	230
Rated electrical power	W	2 (3)	2 (3)	2 (3)	2 (3)	2 (3)	2 (3)
Warm-up time from 12-75 °C with electric heating element	h	3 (2)	3,7 (2,5)	4,5 (3)	5,6 (3,7)	5,6 (3,7)	7,5 (5)
MIX 37 °C (temperature of the water in the water tank: 75 °C; water temperature of supply water: 12 °C)	L	195	250	297	378	378	494
Heat exchanger surface area	m ²	0.49	0.65	0.65	0.89	0.89	0.89
Heat exchanger inside volume	L	1.81	3.15	3.15	4.3	4.3	4.3
Weight when empty	kg	32	36	42.5	52.5	56	65

CONNECTIONS

1: Hot water outlet	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator	-	-	-	-	-	-
4: Табло за управление	-	-	-	-	-	-
5: Flange with heating element	-	-	-	-	-	-
6: Heating coil - Feed	G1/2 M	G3/4 F	G3/4 F	G3/4 F	G3/4 F	G3/4 F
7: Heating coil - Return	G1/2 M	G3/4 F	G3/4 F	G3/4 F	G3/4 F	G3/4 F
8: Socket for thermostat	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F

DIMENSIONS

A	mm	1065	1000	1165	1415	1015	1255
B	mm	980	915	1080	1330	930	1170
C	mm	145	175	175	175	190	190
D	mm	385	460	460	460	586	586
E	mm	80	96	96	96	105	105
F	mm	400	474	474	474	600	600
G	mm	32	32	32	32	43	43
I	mm	110	165	165	165	195	195
J	mm	450	450	450	670	450	450
M	mm	-	-	-	1003	560	780